



## AIR POLLUTION CONTROL GENERAL CONSTRUCTION PERMIT (GCP) FOR NONHEATSET SHEET-FED LITHOGRAPHIC PRINTING PRESSES

In accordance with the provisions of Chapter 285, Wis. Stats., and Chapters NR 400 to 499, Wis. Adm. Code, the owner/operator identified below is hereby granted coverage under this permit and is authorized to construct and operate nonheatset sheetfed lithographic printing presses within a direct stationary source in conformity with the conditions herein until such time that the units are granted coverage under an Operation Permit or a General Operation Permit.

FACILITY IDENTIFICATION NUMBER (FID) [XXXXXXXXXX]

XXXXXXXXXX-GCP08i, where the nine letters of X represent the Facility Identification Number (FID) for the applicant and -08i represents the Nonheatset Sheet-fed Lithographic Printing Synthetic Minor Source General Construction Permit issued in the State of Wisconsin for Minor Facilities.

PERMIT NUMBER. This is a General Construction Permit. This General Construction Permit is not issued to an individual facility. This General Construction Permit will be issued once for use by sources that demonstrate that the source qualifies for coverage under this General Construction Permit. Therefore there is no source specific FID or Permit Number for this General Construction Permit. Instead, this permit will be released for coverage to an individual applicant as Permit Number

STACK NUMBER(S): <As provided by the permit application >

EMISSIONS UNIT NUMBER(S): <As provided by the permit application >

Facility Name: <As provided by permit application >

Street Address:

Responsible Official, & Title:

This authorization requires compliance by the permit holder with the emission limitations, monitoring requirements and other terms and conditions set forth in this permit. The authority for the permit holder to construct, modify, replace and/or reconstruct any printing unit covered under this general construction permit expires eighteen (18) months from the date this permit is released to the facility. This approved period to construct, modify, replace and/or reconstruct may be extended for up to 18 months upon request for cause, prior to expiration, unless otherwise specified by this general construction permit. The conditions of this general construction permit are permanent and may only be revised through revocation of coverage under the general construction permit, through revision of the general construction permit, or through issuance and release for coverage of a new general construction permit.

Dated at Madison, Wisconsin, June 15, 2007

STATE OF WISCONSIN  
DEPARTMENT OF NATURAL RESOURCES  
For the Secretary

By Jeffrey C. Hanson  
Jeffrey C. Hanson  
Permits and Stationary Source Modeling Section Chief

### **Applicability**

This permit applies to nonheatset lithographic sheetfed printing units and associated operations (i.e. “the project”) identified on the cover page to this permit and that meet the following criteria:

- The permittee elects to restrict (e.g. “cap”) actual emissions from the printing units to below 100 tons of volatile organic compounds per year and, if that cap were not in place, the printing units’ total unrestricted potential-to-emit would exceed that level.
- The facility, prior to construction, is classified as a minor source under chs. NR 405 and NR 408, Wis. Adm. Code.
- The facility will not be required, as a result of the proposed project, to obtain a construction permit for one or more new or existing emissions units at the facility, including printing units, under ch. NR 405 or 408.
- The printing units will be located at a facility that will not have the potential-to-emit Federal Hazardous Air Pollutants (HAPs) greater than 10 TPY for each individual and individual category of Federal HAP or greater than 25 TPY for all Federal HAPs combined.
- The facility does not claim any exemptions under s. NR 422.03(4), Wis. Adm. Code, for which it might be qualified.

A “Federal Hazardous Air Pollutant (HAP)” means any pollutant that is listed as a hazardous air pollutant under section 112 (b) of the Clean Air Act (42 USC 7412 (b)).

“Associated operations” means operations that, in addition to operation of a printing unit to print on a substrate during production, are necessary in order to create final printed products or to maintain the ability of a printing unit to operate.

### **Previously Established Emission Limitations**

#### **Previously Issued Construction Permits**

This construction permit may be used to provide coverage of groups of sources (e.g. nonheatset sheet-fed lithographic printing presses) that are in the same source category (e.g. nonheatset lithographic printing) and that have been permitted under a construction permit which contained restrictions on potential-to-emit VOCs based on a five-year window netting analysis under ch. NR 408, Wis. Adm. Code. In these cases, a separate general construction permit must be used for each group of sources, and the original construction permit restrictions on PTE from each group of sources shall still apply, in addition to any restrictions on PTE contained in this construction permit.

#### **Previously Issued Permits**

To qualify for coverage under this general construction permit, the permittee shall submit an application to the Department for each existing permit that contains conditions that apply to one or more sources covered under this general construction permit. These applications shall request the Department to revise the variant conditions in those permits to be consistent with the conditions in this general construction permit.

### **Source Elections**

The nonheatset sheet-fed lithographic printing presses and associated operations covered by this permit are subject to s. NR 424.03, Wis. Adm. Code, and the Department considers each press (including its associated operations) to be part of a separate process line. Under s. NR 424.03(2)(b) and (c), Wis. Adm. Code, 85% emissions control of organic compound emissions is required, or, where 85% control is demonstrated to be technologically infeasible, the permittee must use the latest available control techniques (LACT) and operation practices demonstrating best current technology, as approved by the Department [s. NR 424.03(2)(c), Wis. Adm. Code]. As an alternative to the 85% control requirement, the owner or operator can elect under s. NR 424.03(3), Wis. Adm. Code, to meet the RACT requirements in s. NR 422.142, Wis. Adm. Code. By submitting an application for this permit, the owner or operator is informing the Department of this election, and the Department is approving the request by granting coverage under this permit. This permit requires that each nonheatset sheet-fed lithographic printing process line comply with the RACT requirements in s. NR 422.142, Wis. Adm. Code.

Facilities and associated industrial cleaning operations for which coverage under this general construction permit is granted are potentially subject to the requirements of s. NR 423.035, Wis. Adm. Code, the Industrial Cleaning

Operations Rule. If applicable, requirements of this regulation will be stated in the operation permit that covers industrial solvent cleaning equipment and equipment not granted coverage under this permit that may exist at the facility.

## PART I

### A. OPERATIONAL REQUIREMENTS

- (1) The permittee shall meet the following requirements:
- (a) When printing on a substrate other than metal, metal-foil or plastic, use a fountain solution that has a VOC content as applied of no more than one of the following:
    - (i) 5.0% by weight, or;
    - (ii) 8.5% by weight if the fountain solution is refrigerated to 60°F or less
  - (b) When printing on a metal, metal-foil or plastic substrate, use a fountain solution that has a VOC content as applied of no more than one of the following:
    - (i) 5.0% by weight, or;
    - (ii) 13.5% by weight if the fountain solution contains any restricted alcohol and is refrigerated to 60°F or less. "Restricted alcohol" means an alcohol that contains only one hydroxyl (–OH) group and less than 5 carbon atoms.
  - (c) Use blanket and roller cleaning solutions that, as applied, meet one of the following:
    - (i) A VOC content of no greater than 30% by weight, or;
    - (ii) A vapor pressure for each VOC component of less than or equal to 10 mm Hg at 20°C (68°F).
  - (d) The permittee may use blanket and roller cleaning solutions that do not meet the limitations in I.A.(1)(c), provided that the total amount of those blanket and roller cleaning solutions used at the facility over any 12 consecutive months is less than or equal to one of the following:
    - (i) If the facility does not print on a plastic substrate, 55 gallons
    - (ii) If the facility prints on a plastic substrate, 165 gallons[s. 285.65(7), Wis. Stats., and ss. NR 424.03(3), NR 422.142(2)(b), and NR 422.142(2)(c), Wis. Adm. Code.]
- (2) In order to receive credit for retention<sup>1</sup> of VOC-containing materials in shop towels, wipes, pads and other media used for manual cleaning operations, the permittee shall handle the soiled media in a manner that minimizes solvent evaporation and spills and shall meet one or more of the following requirements to receive corresponding credit:
- (a) 50% VOC retention (50% emitted as VOCs) may be applied for a cleaning solution if it contains less than 30% VOC by weight or a has a VOC composite vapor pressure of no more than 10 mm Hg at 68°F, or
  - (b) 40% VOC retention (60% emitted as VOCs) may be applied for a cleaning solution if its VOC composite vapor pressure is greater than 10 mm Hg but less than 25 mm Hg at 68°F, or contains more than 30% VOC by weight. [s. 285.65(7), Wis. Stats.]
- (3) No person may cause, allow or permit organic compounds to be used or handled without using good operating practices and taking reasonable precautions to prevent the spillage, escape or emission of organic compounds (including VOCs), solvents or mixtures. Such precautions shall include, but are not limited to,
- (a) use of caution to prevent spillage or leakage when filling tanks
  - (b) use of caution when performing the disposal of any VOC containing materials. The permittee shall perform the disposal by a method approved by the Department, such as incineration, recovery for reuse, or transfer in closed containers to an acceptable disposal facility
  - (c) keep each VOC-containing material in a closed container, except when in use at the facility, when handled during solvent recovery or during transfer to another container, or when filling, draining, or performing cleanup operations. VOC-containing materials include but are not limited to as-received materials, as-applied materials, shop towels, wipes, pads and other media used for manual cleaning operations
  - (d) use measures such as written plans, work instructions, training documents, signage, or verbal instructions to establish operating practices that prevent the spillage, escape or emission of organic compounds from the handling, transfer, storage and disposal of VOC-containing materials. [ss. NR 419.03(2), NR 419.04(2), NR 406.16(1)(d), and NR 439.04(1)(d), Wis. Adm. Code, and s. 285.65(7), Wis. Stats.]

<sup>1</sup> Note that the Department memorandum titled "Guidelines for Determining Emissions from Lithographic Printing Facilities" and dated August 21, 1997, also contains VOC emission factors that the permittee may use to calculate emissions from inks, blanket and roller wash, and clean-up solvents. Consult that document for further details.

(4) The permittee may not cause, allow, or permit the total actual emissions of VOCs from all nonheatset lithographic sheet-fed printing units, and their associated operations<sup>2</sup>, covered under this permit to exceed 99.9 tons of volatile organic compounds per year, calculated<sup>3</sup> monthly as the cumulative total over the most recent period of twelve consecutive calendar months. [s. 285.65(7), Wis. Stats.]

---

<sup>2</sup> “Associated operations” means operations that, in addition to operation of a printing unit to print on a substrate during production, are necessary in order to create final printed products or to maintain the ability of a printing unit to operate.

<sup>3</sup> This permit implements the USEPA’s formula-based approach for demonstrating compliance with this restriction on potential-to-emit. See the USEPA’s Technical Support Document, section 6.3.1, at <http://www.epa.gov/ttn/emc/cam/tsd.pdf>

## B. RECORDKEEPING REQUIREMENTS

(1) If a material received from an off-site supplier is intended for use by one or more nonheatset sheet-fed lithographic printing presses or by an associated operation and if the material contains greater than 1% VOC by weight, then at or before the time of application or use the permittee shall

(a) identify and record the material or the class of similar materials to which it belongs, using a unique name or identification code

(b) determine by specification or by calculation and then record:

(i) the VOC content, in pounds of VOC per gallon or in weight percent, of the material or class, and

(ii) when necessary to demonstrate compliance with a weight percent limit in I.A.(1) or to make a calculation under I.B.(2), determine and record the density, in pounds per gallon, of the material or class.

(c) when determining the VOC content or other property for each material in a class of similar materials, use the specifications for the material which has the highest VOC content in that class.

(d) to determine VOC content or density, the permittee may use one or more of the following specification documents: testing results, the Material Safety Data Sheet from the supplier or manufacturer, general chemical literature, or a compositional analysis (formulation) of the material. When a document states a range of values for a specification, the permittee shall use the value that results in the worst-case VOC content. The permittee may elect to use a VOC content of 100% for materials lacking documentation.

(e) determine and record the vapor pressure, in units of mmHg at 20°C, of each VOC component in each blanket and roller cleaning solution for which the permittee elects to meet the requirement under I.A.(1)(c)(ii).

(f) record the calculations, supplier formulation, and other data used to determine the VOC content of each material and class of similar materials.

[ss. NR 406.16(1)(d), NR 439.04(5)(a), and NR 422.145(4), Wis. Adm. Code]

(2) In order to meet a limitation under I.A.(1)(a), (b), or (c)(i) on a fountain solution or blanket and roller cleaning solution that is diluted with water or is a mixture of two or more materials, the permittee shall use an applicable method below to determine and record the VOC content, in weight percent, of the as-applied material, and for each mixture prepared manually according to a distinct formulation the permittee shall monitor and record the amount of each material used to prepare the mixture:

(a) in lieu of a method otherwise required under (b), (c), or (d), the permittee may test and record the as-applied VOC content of the material or mixture using an applicable method under I.C.

(b) whenever a material is automatically or manually prepared for use, the permittee shall determine and record the VOC content of and identify the distinct formulation used to prepare the material, such that the VOC content of a distinct formulation is calculated only once according to the following formula<sup>4</sup>:

$$V_{Applied} = \left[ \frac{\sum_1^n (C_i Q_i)}{\sum_1^n (Q_i d_i)} \right]$$

(c) whenever a newly-prepared material is added to a previously-prepared as-applied material that has the same VOC content, the permittee may use that VOC content for the mixture without further calculation.

(d) whenever a single material (e.g. alcohol) is added to an as-applied material (e.g. fountain solution) that was prepared from a formulation with a lower VOC content than the single material, the permittee shall calculate and record the new as-applied VOC content using the following formula:

<sup>4</sup> Note that this formula, as written, can be used in two ways. First, it can calculate the VOC content of a batch on an absolute basis, where the number of gallons actually added are used to make the calculation. Second, it can be used to calculate the VOC content of the batch on the basis of one total gallon, where the  $Q_i$  values are actually fractions of a gallon that add up to one. The set of these fractional values define the "distinct formulation" of the material, since they are the ratios that can be used to prepare a batch of that same material in any amount required.

$$V_{New} = \left( \frac{C_{Old} Q_{Old} + \sum_1^m (C_k Q_k)}{Q_{Old} d_{Old} + \sum_1^m (Q_k d_k)} \right)$$

where  $\{C_k\}$ ,  $\{d_k\}$ , and  $\{Q_k\}$  in the formula above correspond to the materials being added to an amount,  $Q_{Old}$ , of the as-applied material, and

where the  $C_{Old}$  and  $d_{Old}$  data are determined either by a test method under I.C., or by the following calculations using the  $\{C_i\}$ ,  $\{d_i\}$ , and  $\{Q_i\}$  data from the current as-applied material's distinct formulation:

$$C_{Old} = \left[ \frac{\sum_1^n (C_i Q_i)}{\sum_1^n (Q_i)} \right] \qquad d_{Old} = \left[ \frac{\sum_1^n (Q_i d_i)}{\sum_1^n (Q_i)} \right]$$

where:

$V_{Applied}$  or  $V_{New}$  =the VOC content of the as-applied material according to its current or modified formulation (e.g. increased VOC content), respectively, in units of %VOC by weight;

$n$  =the number of materials that were mixed together to prepare a given as-applied fountain solution or blanket and roller cleaning solution from its distinct formulation;

$m$  =the number of materials added to a batch that already contains a mixture;

$C_i$  =the VOC content of the  $i$ th material (including water), in units of pounds VOC per gallon, that was added to prepare a batch of a given material using its distinct formulation;

$Q_i$  =the amount of the  $i$ th material (including water) that was added according to a distinct formulation to prepare a given as-applied material, in gallons;

$d_i$  =the density of the  $i$ th material, in units of pounds per gallon;

$Q_{Old}$  =The amount of the previous mixture of the as-applied material that was present when supplemental material was added, in units of gallons;

$C_{Old}$  =the VOC content of the previous mixture of as-applied material, in units of pounds per gallon, before supplemental material was added;

$d_{Old}$  =the density of previous mixture, in units of pounds per gallon, before supplemental material was added;

$d_k$  =the density of the  $k$ th supplemental material being added to prepare a new mixture with a distinct formulation, in pounds per gallon;

$C_k$  =the VOC content of each supplemental material, in pounds VOC per gallon, that was added to the current mixture;

$Q_k$  =the amount of each supplemental material added to the current mixture, in units of gallons.

[s. NR 406.16(1)(d), Wis. Adm. Code]

(3) Whenever a product printed on metal, metal-foil or plastic is under production by one or more presses, the permittee shall determine and record the following for each lithographic printing press that produces the product and for which the permittee elects to meet the requirement under I.A.(1)(b)(ii):

- (a) the dates on which the product was printed by the press, and
- (b) the fountain solutions, as identified under I.B.(1)(a), in use by the press on those dates of production.

<sup>5</sup> Note: Each material  $j$  belongs in one and only one material category  $c$ . For example: if a specific ink is second in the list of inks used by a printing unit (e.g. a press), then this specific ink corresponds to  $j=2$ . If the category for inks is third in a list, then  $c=3$ . Thus,  $E_{c,2} = E_{3,2}$ , and this term will be used to calculate  $E_3$  (the emissions during the month from usage of all inks).

<sup>6</sup> For example, when the permittee uses this formula to calculate  $E_c$  for  $c=2$ , then  $E_2 = E_c$ , and the permittee shall use that quantity for the purpose of making the calculation in the next condition. The same is true for other values of  $c$ .

[s. NR 406.16(1)(d), Wis. Adm. Code]

(4) For each fountain solution for which the permittee elects to meet the requirement under I.A.(1)(a)(ii) or (b)(ii), the permittee shall monitor and record the temperature of the fountain solution reservoir at least once per 8-hour shift of operation. [ss. NR 422.142(3), NR 422.142(4)(b), Wis. Adm. Code, and NR 406.16(1)(d), Wis. Adm. Code]

(5) For each distinct fountain solution formulation identified under I.B.(2)(b) the permittee shall determine and record the chemical name of each restricted alcohol, if any, contained in the fountain solution formulation, where “restricted alcohol” means an alcohol which contains only one hydroxyl (-OH) group and less than 5 carbon atoms. [ss. NR 422.142(2)(b)1. and 4., and NR 407.09(4)(a)3.b., Wis. Adm. Code]

(6) Within 15 days after the end of each calendar month, the permittee shall determine and record the total volume, in gallons, of all as-applied blanket and roller cleaning solutions used during the previous calendar month that did not meet the emission limitations of I.A.(1)(c) and then shall calculate and record the total volume, in gallons, of these cleaning solutions that were used during the previous 12 calendar months. [ss. NR 422.142(2)(c)2., NR 422.142(4)(e), and NR 406.16(1)(d), Wis. Adm. Code]

(7) If the permittee claims credit for retention under I.A.(2)(a) or (b), then the permittee shall determine and record the VOC composite vapor pressure, as applied, of each material (e.g. solvent) used for manual cleaning operations. To determine this quantity, the permittee may use the VOC composite vapor pressure reported on the material’s MSDS or other supplier specification document. The permittee may derive VOC composite vapor pressure mathematically by using the following formula with data for the vapor pressure of each component in the material, as reported on an MSDS or in another supplier specification document that reports vapor pressure test results:

$$P_c = \sum_{i=1}^n \left[ \frac{\frac{W_i P_i}{M_i}}{\frac{W_w}{M_w} + \frac{W_e}{M_e} + \sum_{i=1}^n \left( \frac{W_i}{M_i} \right)} \right]$$

Where:

- $W_i$  =Weight of the “i”th VOC compound, in grams
- $W_w$  =Weight of water, in grams
- $W_e$  =Weight of exempt compound (includes all non-VOC compounds), in grams
- $M_i$  =Molecular weight of the “i”th VOC compound, in g/g-mole
- $M_w$  =Molecular weight of water, in g/g-mole
- $M_e$  =Molecular weight of exempt compound (includes all non-VOC compounds), in g/g-mole
- $P_c$  =VOC composite partial pressure at 20°C, in mm Hg
- $P_i$  =Vapor pressure of the “i”th VOC compound at 20°C, in mm Hg

[s. NR 406.16(1)(d), Wis. Adm. Code]

(8) Whenever the permittee elects under condition I.B.(2)(a) to test an alcohol-containing fountain solution, the permittee shall use a hydrometer, equipped and calibrated according to the requirements under I.C.(4), to automatically or manually monitor and record the specific gravity of the fountain solution at least once per 8-hour shift. Using the test data and literature data for the water and alcohol’s relevant physical properties, the permittee shall calculate for each test either the VOC content of the fountain solution, in percent by weight, or the specific gravity that corresponds to the VOC content of the solution’s reported formulation. [s. NR 406.16(1)(d), Wis. Adm. Code]

(9) Within 15 business days after the end of each calendar month the permittee shall:

(a) determine and record the sum total amount, in units of gallons, of each VOC-containing material (or of the class of

similar materials representing the material) that was used during the previous calendar month by the nonheatset sheet-fed lithographic printing units covered under this permit and their associated operations, according one of the following usage monitoring methods:

- (i) monitor the material's (or class's) inventory, consumption, or purchase data such that the data segregates the actual use of the material (or class) by all (combined) nonheatset sheet-fed lithographic printing units and associated operations covered under this permit from the usage by other units and operations at the facility, and then calculate the material usage for all units and operations covered under this permit using material balances, excluding from the totals any amount of material returned to inventory or recovered as waste and that was not already excluded from the totals for other operations at the facility (e.g. double-counted), or
  - (ii) allocate the usage of the material (or of its class) to all (combined) nonheatset sheet-fed lithographic printing units and associated operations covered under this permit, using an alternative method submitted with the permit application and approved by the Department.
  - (iii) The permittee may change the monitoring method after coverage is granted under this permit after gaining Department approval of that method. If the Department does not act within 60 days of a receipt of a request to use an alternative method, the method shall be deemed approved.
- (b) determine and record within 15 days after the end of each calendar month the actual amount, in gallons, of each VOC-containing cleaning solvent recovered during previous calendar month, if the permittee utilizes a solvent recovery operation to reclaim solvent from shop towels or other manual cleaning media.
- (c) record all data and calculations used to determine the quantities of material determined and recorded under (a) and (b).

[ss. NR 407.09(1)(c)1., (4)(a)1.&(4)(a)3.b., Wis. Adm. Code]

(10) The permittee shall use the following two equations to calculate and record within 15 days after the end of each calendar month the total actual emissions of VOC from each of the 4 material categories used by the units and operations covered under this permit during the most recent calendar month,  $E_c$ ,

(a) Using the following equation for each material  $j$ , the permittee shall calculate the total emissions of VOCs during the previous calendar month,  $E_{c,j}$ , in pounds, due to the use of that material<sup>5</sup>,

$$E_{c,j} = U_j \times C_j \times \left( \frac{100\% - R_c}{100\%} \right) \times \left\{ 1 - \left( \frac{P_c}{100\%} \right) \times \left( \frac{L_d}{100\%} \right) \right\}$$

where

$U_j$  =the amount, in gallons or pounds (as appropriate), of the material  $j$  used by units and operations covered under this permit during the most recent calendar month

$C_j$  =the average amount (content) of the pollutant of interest in the material  $j$ , measured in pounds per gallon or weight percent (as appropriate)

$R_c$  =the % of the pollutant in the material that is retained and not emitted, according to the retention credit that the material qualifies for under I.A.(2), if any. If the material does not qualify for a retention credit, the permittee shall assume that  $R_c = 0\%$ .

$P_c$  =the % of the pollutant's emissions that is captured prior to control

$L_d$  =the % of the pollutant's emissions controlled by the control device  $d$  (if  $d \geq 1$ )

and where

for all nonheatset sheet-fed lithographic printing inks, coatings, and thinners used in as-applied formulations,  $c = 1$ , and

$R_1 = 0\%$ .

$P_1 = 0\%$  or, if equipped with a capture system, the capture efficiency demonstrated for that system.

$L = 0\%$  or, if equipped with a control device, the control efficiency demonstrated for that device.

for all fountain solutions,  $c = 2$ , and

$R_2 = 0\%$

$P_2 = 0\%$  or, if equipped with a capture system, the capture efficiency demonstrated for that system.

$L = 0\%$  or, if equipped with a control device, the control efficiency demonstrated for that device.

for all automatic and manual blanket and roller cleaning solutions,  $c = 3$ , and

$R_3$  =the percent retention for which the permittee qualifies in accordance with condition I.A.(2).  
 $P_3$  =0% or, if equipped with a capture system, the capture efficiency demonstrated for that system.  
 $L$  =0% or, if equipped with a control device, the control efficiency demonstrated for that device.

for all other solvents and other VOC-containing materials not categorized above,  $c =4$ , and

$R_4$  =0%  
 $P_4$  =0%  
 $L$  =0%

(b) Using the following equation<sup>6</sup> for each material category  $c$ , the permittee shall calculate the total emissions, in pounds, of VOCs from that category of materials during the previous calendar month,

$$E_c = E_{c,1} + E_{c,2} + E_{c,3} + \dots + E_{c,m}$$

where  $c$  is the number representing one of the material categories numbered 1 to 4,  
where the facility has a total of  $m$  materials used during the most recent calendar month for that category,  
where each term ( $E_{c,1}$  through  $E_{c,m}$ ) represents the emissions resulting from the total usage of one of the materials in the material category  $c$  during the month.

[ss. NR 407.09(4)(a)1. and (4)(a)3.b., Wis. Adm. Code]

(11) The permittee shall use the following equation to calculate and record within 15 days after the end of each calendar month the total actual emissions,  $E_M$ , of VOCs from the units and operations covered under this permit during the previous calendar month, in units of tons,

$$E_M = \left( \frac{E_1 + E_2 + E_3 + E_4}{2000} \right)$$

where units and operations covered under this permit during the previous calendar month used 4 categories of VOC-containing materials, and

where  $E_1$  through  $E_4$  were calculated under the previous condition for each category.

[ss. NR 407.09(4)(a)1. and (4)(a)3.b., Wis. Adm. Code]

(12) Within 15 days after the end of each calendar month the permittee shall use the following equation to calculate and record  $E_T$ , which is the total VOC emissions, in tons, from all nonheatset sheet-fed lithographic printing units covered under this permit, and their associated operations, during the most recent 12 consecutive calendar months,

$$E_T = E_{M1} + E_{M2} + E_{M3} + E_{M4} + E_{M5} + E_{M6} + E_{M7} + E_{M8} + E_{M9} + E_{M10} + E_{M11} + E_{M12}$$

where the terms  $E_{M1}$ ,  $E_{M2}$ ,  $E_{M3}$ , etc., are the total VOC emissions, in tons, from all nonheatset sheet-fed lithographic printing units and associated operations covered under this permit.

[ss. NR 407.09(4)(a)1. and (4)(a)3.b., Wis. Adm. Code]

### **C. METHODS FOR DETERMINING VOC CONTENTS**

(1) Whenever the Department requires compliance testing of an ink or coating that is not thin-film-radiation-cured, in order to determine the VOC content or density of the material, the permittee shall use U.S. EPA Method 24 in 40 CFR part 60, Appendix A, to determine organic solvent content, unless the Department has approved the permittee to use an alternative method. For thin-film-radiation-cured coatings and inks the permittee may determine VOC content by specification or calculation, using a document allowed under I.B.(1)(c).

[ss. NR 406.16(1)(d) and NR 439.06(3)(b), Wis. Adm. Code]

(2) Whenever compliance testing of a clean-up solvent, thinner, or other material (except an ink or coating) is required in order to determine the VOC content or density of the material, the permittee shall use a method to determine organic solvent content and density that has been approved by the Department. The permittee may use U.S. EPA Method 24 in 40 CFR part 60, Appendix A, to determine VOC content and density of these materials. [ss. NR 406.16(1)(d) and NR 439.06(3)(b), Wis. Adm. Code]

(3) Whenever compliance testing is required in order to determine the VOC composite vapor pressure of a material or to determine the vapor pressure of each component in a material, the permittee shall use method ASTM D2879-97 in 40 CFR part 60, Appendix A, incorporated by reference in s. NR 484.10(39m), unless the Department has approved the permittee to use an alternative method. [s. NR 439.06(3)(a), Wis. Adm. Code]

(4) Whenever compliance testing is required in order to determine the VOC content or density of a fountain solution that consists only of water and a single alcohol, the permittee shall use an ASTM-rated hydrometer that is equipped with an ASTM-rated thermometer that has temperature correction or that is subsequently adjusted for temperature, to measure the specific gravity of the solution. For each test the permittee shall use the average of all readings during that test to determine and record the solution's specific gravity. Before conducting the test, the permittee shall calibrate the monitoring device for the type of alcohol in the fountain solution, using a standard solution. Unless the permittee elects to test with an automatic hydrometer device, the permittee shall conduct the test manually and take 3 successive readings within a 10 minute period. If the permittee elects automatic testing, the permittee shall take at least one reading per hour of operation, using an automatic hydrometer device that has a visual, analog, or digital readout with an accuracy of  $\pm 0.5\%$  of the quantity being measured. [ss. NR 439.055(3), (4), (5), and (6), Wis. Adm. Code]

#### **D. HAZARDOUS AIR POLLUTANT REQUIREMENTS**

- (1) The permittee may emit to ambient air a hazardous air contaminant that is listed under Table A of chapter NR 445, Wis. Adm. Code, and that does not have a control requirement listed under column (i) of Table A, only if the facility emissions of the contaminant meet at least one of the following conditions (a), (b), (c), or (d):
- (a) the contaminant is released to ambient air by general building ventilation sources and all applicable thresholds in column (h) of Table A for the contaminant are stated either in 1-hour or 24-hour average time periods
  - (b) the contaminant is released to ambient air by general building ventilation sources and all of the following requirements are met for the contaminant:
    - (i) at least one applicable threshold in column (h) of Table A for the contaminant is stated in terms of an annual time period
    - (ii) the contaminant has a threshold limit value established by the American Conference of Governmental Industrial Hygienists, in the Threshold Limit Values for Chemical Substances and Physical Agents and Biological Exposure Indices for 2000
    - (iii) the permittee demonstrates to the department that it is in compliance with applicable occupational safety and health administration requirements
  - (c) the contaminant is released in quantities that do not exceed the appropriate threshold level in columns (c) to (f) of Table A, provided that the stack that vents the emissions meets the following criteria:
    - (i) the emissions are from an unobstructed discharge point and
    - (ii) the stack is oriented in an upward direction within 10 degrees of vertical
  - (d) the owner or operator limits emissions so as not to cause an ambient air quality concentration off property that exceeds column (g) of Table A, where applicable  
[ss. NR 445.07(1), NR 445.07(5)(d)1, Wis. Adm. Code]
- (2) The permittee may emit to ambient air a hazardous air contaminant that is listed under Table A of chapter NR 445, Wis. Adm. Code, that does have a control requirement listed under column (i) of Table A, only if the contaminant has a unit risk factor established by either the USEPA or the California Air Resources Board and if the facility emissions of the contaminant meet at least one of the following conditions (a) or (b), where inhalation impact is defined under s. NR 445.08(2)(c), Wis. Adm. Code:
- (a) the inhalation impact off property from each individual contaminant with a control requirement in column (i) does not exceed 1 in  $10^{-6}$  (1 in a million), or
  - (b) the inhalation impact from all contaminants with a control requirement in column (i) does not exceed 1 in  $10^{-5}$  (1 in 100,000)  
[ss. NR 445.07(1), NR 445.08(2)(c), Wis. Adm. Code]
- (3) The permittee may not cause, allow, or permit from the facility at which the printing unit(s) covered by this general permit are located the emission of Federal Hazardous Air Pollutants (HAPs) greater than 10 tons per year for each individual and individual category of Federal HAP or greater than 25 tons per year for all Federal HAPs combined. Federal HAP emissions shall be calculated no less frequently than monthly as the cumulative total over the most recent period of twelve consecutive calendar months. [s. 285.65(7), Wis. Stats.]

## **E. REPORTING REQUIREMENTS**

(1) Unless otherwise specified in a construction permit covering the facility, the permittee shall submit an annual certification of compliance with the terms and conditions of this permit, along with an annual monitoring summary report containing the monitoring results required in this permit, to the Wisconsin Department of Natural Resources, Bureau of Air Management (AM/7), Compliance Team Leader, P.O. Box 7921, Madison, WI 53707-7921, or to the attention of Air Program Compliance at the address of the Department's Service Center that is located nearest to the facility. Compliance certifications and monitoring summary reports made to the Department shall cover all equipment covered by air pollution control operation permits, including those granted coverage under this general construction permit.

- (a) The time period to be addressed by the report is the January 1 to December 31 period which precedes the report, or the time period for the report required by an existing permit, if any. However, the report does not need to address any calendar month during which the permittee was not subject to this permit for at least part of the month.
- (b) The reports shall be submitted to the Service Center Office (or Central Office) within 60 days after the end of each reporting period.
- (c) The information included in the reports shall comply with the requirements of Part II Section N of this permit, including but not limited to the information required under s. NR 439.03(8), Wis. Adm. Code.
- (d) Each report shall be certified by the responsible official as to the truth, accuracy and completeness of the report.
- (e) The methods used to determine the permittee's compliance status shall be the same methods which are required under s. NR 407.09(1)(c)1.

[ss. NR 439.03(1)(c), NR 439.03(8), and NR 439.03(10), Wis. Adm. Code]

(2) All records required under this construction permit shall be retained and maintained for at least five (5) years and shall be made available to Department personnel upon request during normal business hours. [s. NR 439.04, s. NR 439.05, & s. NR 406.16(1)(d), Wis. Adm. Code]